


F28WW


28° WIRE-WELD FRAMING NAILER 90MM MAX


Diameter: 2.8 - 3.3mm
Length: 50 - 90mm





Features


- 


Magnesium Housing
- 


Rubber Comfort Grip
- 


Serrated Tip
- 


No-Mar-Tip
- 

Dial-A-Depth
- 

Push Button Depth Control
- 

Sequential Trip
- 

Anti Slip Bumpers
- 

Compact Nose
- 

Carry Case

SPECIFICATION

| | | | |
|-------------------------|----------------------------|--|-----------------------------|
| Power type | Pneumatic | Operating pressure | 4.80 - 8.30 BAR |
| Weight | 3.50 kg | | 70.00 - 120.00 PSI |
| Width | 133 mm | Air Consumption Ltr.per shot @ 5.6 bar | 2.47 |
| Length | 508 mm | Air fitting thread type | 1/4 BSP |
| Height | 355 mm | Noise | LPA 1sd 96.30 |
| Magazine capacity (max) | 90 | | LWA 1sd 100.10 |
| Series Fasteners: | | | LPA 1s, 1m 87.10 |
| Diameter (mm) | 2.8 (min) 3.3 (max) | Vibration / Uncertainty | 2.47 / N/A m/s ² |
| Length (mm) | 50 (min) 90 (max) | | |
| Head (mm) | 7.5 (min) 7.5 (max) | | |
| Collation type | EE->lang->language[""]; ?> | | |