

SAFETY DATA SHEET

Revision Date 24-May-2018 Version 2

1. IDENTIFICATION

Product identifier

Product Name Gumout High Mileage Fuel Injector Cleaner

Other means of identification

Product Code 10707

Document SKU: 510013, 800001363

Recommended use of the chemical and restrictions on use

Recommended Use Fuel injector cleaner. Consumer Use.

No information available Uses advised against

Details of the supplier of the safety data sheet

Supplier Address Manufacturer Address Manufactured and Distributed by:

ITW Global Brands 16200 Park Row, Suite 120

Houston, TX 77084

Distributor May Also Be Distributed by:

ITW Permatex Canada 101-2360 Bristol Circle

Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

Company Phone Number 1-855-888-1988

24-hour emergency phone number (CHEMTREC) 1-800-424-9300 or 1-703-527-3887 (U.S.)

(RMPDC) 1-877-504-9352 (U.S.)

SDS@itwgb.com E-mail address

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity	Category 1B
Aspiration toxicity	Category 1
Flammable liquids	Category 4

Label elements

Emergency Overview

Signal word Danger

May cause cancer

May be fatal if swallowed and enters airways

Combustible liquid



Appearance Yellow Physical state Liquid Odor Hydrocarbon

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- May be harmful in contact with skin

Unknown acute toxicity

4.1 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance(s)

Chemical Name	CAS No	Weight-%
DISTILLATES (PETROLEUM),	64742-47-8	60 - 100
HYDROTREATED LIGHT		
NAPHTHALENE	91-20-3	0.1 - 1

Any concentration shown as a range is due to batch variation.

4. FIRST AID MEASURES

Description of first aid measures

General advice If symptoms persist, call a physician.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

Skin contact Immediate medical attention is not required. Wash off immediately with soap and plenty of

water while removing all contaminated clothes and shoes. If skin irritation persists, call a

physician.

Immediate medical attention is not required. If symptoms persist, call a physician, Move to Inhalation

fresh air in case of accidental inhalation of vapors or decomposition products.

Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth Ingestion

to an unconscious person. Call a physician. Do NOT induce vomiting.

Self-protection of the first aider Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO2, sand, earth, water spray or regular foam, Use, Dry chemical, Carbon dioxide (CO2), Water spray (fog), Alcohol resistant foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Combustible material. Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes and Personal precautions

inhalation of vapors. Use personal protective equipment as required. Remove all sources of ignition. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Pay attention to flashback. Take precautionary measures against static discharges.

Environmental precautions

See section 12 for additional ecological information. Do not flush into surface water or **Environmental precautions**

sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent product

from entering drains.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Soak up with inert absorbent material. Dam up. Pick up and transfer to properly labeled

containers. Take precautionary measures against static discharges.

Clean contaminated objects and areas thoroughly observing environmental regulations. Prevention of secondary hazards

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use with local exhaust ventilation. All equipment used when handling the product must be

grounded. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use

personal protective equipment as required. Do not breathe

dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapors).

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of

children. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated

place. Keep away from heat. Keep in properly labeled containers.

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
NAPHTHALENE	TWA: 10 ppm	TWA: 10 ppm	IDLH: 250 ppm
91-20-3	S* '	TWA: 50 mg/m ³	TWA: 10 ppm
		(vacated) TWA: 10 ppm	TWA: 50 mg/m ³
		(vacated) TWA: 50 mg/m ³	STEL: 15 ppm
		(vacated) STEL: 15 ppm	STEL: 75 mg/m ³
		(vacated) STEL: 75 mg/m ³	G

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protectionUse NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical stateLiquidAppearanceYellowOdorHydrocarbon

Odor threshold No information available

Setaflash Closed Cup

Values Remarks • Method **Property**

Not applicable рΗ No information available

Melting point / freezing point

Boiling point / boiling range

84 °C / 183 °F Flash point

Evaporation rate No information available Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: No information available Lower flammability limit: No information available Vapor pressure No information available Vapor density No information available Relative density No information available

Water solubility Negligible

No information available Solubility in other solvents Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available **Dvnamic viscosity** No information available **Explosive properties** No information available Oxidizing properties No information available

Other Information

Softening point No information available Molecular weight No information available

VOC Content (%) 0.3

Density 0.83 g/cm3

No information available **Bulk density**

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal use

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract. May cause central nervous system depression with

nausea, headache, dizziness, vomiting, and incoordination. Intentional misuse by

deliberately concentrating and inhaling contents may be harmful or fatal.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis.

Ingestion

Ingestion may cause irritation to mucous membranes. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT 64742-47-8	> 5000 mg/kg(Rat)	> 2000 mg/kg(Rabbit)	> 5.2 mg/L (Rat)4 h
NAPHTHALENE 91-20-3	= 490 mg/kg(Rat)= 1110 mg/kg(Rat)	= 1120 mg/kg(Rabbit)> 20 g/kg(Rabbit)	> 340 mg/m³ (Rat) 1 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicityNo information available.
No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
NAPHTHALENE	A3	Group 2B	Reasonably Anticipated	X
91-20-3		·		

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 5268 mg/kg **ATEmix (dermal)** 2107 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

4.7 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

Disperses in water.

Chemical Name	Partition coefficient
NAPHTHALENE	3.6
91-20-3	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Recover or recycle if possible. Disposal should be in accordance with applicable regional,

national and local laws and regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number U165

Chemical Name	RCRA - Halogenated	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
	Organic Compounds			
NAPHTHALENE	-	-	Toxic waste	-
91-20-3			waste number F025	
			Waste description:	
			Condensed light ends, spent	
			filters and filter aids, and	
			spent desiccant wastes from	
			the production of certain	
			chlorinated aliphatic	
			hydrocarbons, by free	
			radical catalyzed processes.	
			These chlorinated aliphatic	
			hydrocarbons are those	
			having carbon chain lengths	
			ranging from one to and	
			including five, with varying	
			amounts and positions of	
			chlorine substitution.	

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
NAPHTHALENE	Toxic
91-20-3	

14. TRANSPORT INFORMATION

DOT

Proper shipping name: Not regulated

IATA

Proper shipping name: Not regulated

<u>IMDG</u>

Proper shipping name: Not regulated

15. REGULATORY INFORMATION

International Inventories

Complies **TSCA DSL/NDSL** Complies **EINECS/ELINCS** Not determined Not Listed. **ENCS IECSC** Not determined **KECL** Not determined **PICCS** Not determined **AICS** Not determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %	
NAPHTHALENE - 91-20-3	0.1	
SARA 311/312 Hazard Categories		

Acute health hazard Yes **Chronic Health Hazard** No Fire hazard Yes Sudden release of pressure hazard No **Reactive Hazard** No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
NAPHTHALENE 91-20-3	100 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
NAPHTHALENE	100 lb 1 lb	-	RQ 100 lb final RQ
91-20-3			RQ 45.4 kg final RQ RQ 1 lb final
			RQ
			RQ 0.454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

This product contains the following respondence chemicals		
Chemical Name	California Proposition 65	
NAPHTHALENE - 91-20-3	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
1,2,4-TRIMETHYLBENZENE 95-63-6	X	X	X
NAPHTHALENE 91-20-3	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

B3 - Combustible liquid, D2A - Very toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 2 Instability 0

Health hazards 2 Flammability 2 Physical hazards 0 **HMIS** Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 24-May-2018

Revision Note

3

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet