



SPECIALTY TIRE HI-RUN

Main Feature

- ☑ **Aggressive Tread Pattern:** Provides excellent grip on both wet and dry surfaces, suitable for mixed terrain driving.
- ☑ **Durable Compound:** Ensures the tire's longevity, even in challenging environments.
- ☑ **Wide Tread Blocks:** Enhance stability and handling, especially when cornering.
- ☑ **Superior Water Dispersion:** Reduces the risk of hydroplaning by efficiently channeling water away from the contact area.



SU05

Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WD1147	4.10/3.50-4	2	3.8	3.25	3.9	10.6	230	24
WD1148	4.10/3.50-4	4	3.8	3.25	3.9	10.8	350	50
WD1083	4.80/4.00-8	2	4.4	3.75	4.7	16.6	435	20
WD1149	4.80/4.00-8	4	4.4	3.75	4.7	16.6	670	42
WD1084	11X4.00-4	2	3.8	3.25	3.9	10.6	215	22
WD1118	11X4.00-4	4	3.8	3.25	3.9	10.6	330	46
WD1119	11X4.00-5	2	3.8	3	3.9	10.6	210	22
WD1120	11X4.00-5	4	3.8	3	3.9	10.6	325	46
WD1031	13X5.00-6	2	3.8	4.5	5.2	12.2	295	20
WD1121	13X5.00-6	4	3.8	4.5	5.2	12.4	440	40
WD1122	13X6.50-6	4	4.4	5	6.3	13.1	460	28
WD1030	15X6.00-6	2	7.6	4.5	6.1	14.3	365	14



HI-RUN

Main Feature

- ✓ **Aggressive Tread Pattern:** Provides excellent grip on both wet and dry surfaces, suitable for mixed terrain driving.
- ✓ **Durable Compound:** Ensures the tire's longevity, even in challenging environments.
- ✓ **Wide Tread Blocks:** Enhance stability and handling, especially when cornering.
- ✓ **Superior Water Dispersion:** Reduces the risk of hydroplaning by efficiently channeling water away from the contact area.



SU05

Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WD1124	15X6.00-6	4	7.6	4.5	6.3	15	570	30
WD1285	15X6.50-8	2	7.6	5.375	6.1	15	565	28
WD1286	15X6.50-8	4	7.6	5.375	6.1	15	565	28
WD1043	16X6.50-8	2	8.9	5.375	6.5	15.9	415	14
WD1125	16X6.50-8	4	8.9	5.375	6.5	16.1	620	28
WD1126	16X6.50-8	6	8.9	5.375	6.6	16.3	785	42
WD1127	16X7.50-8	2	8.9	5.375	7.2	15.9	475	12
WD1128	16X7.50-8	4	8.9	5.375	7.2	16.1	680	24
WD1129	18X6.50-8	4	5	5	6.5	17.9	770	28
WD1131	18X7.00-8	4	8.8	5.375	7	17.7	785	26
WD1032	18X8.50-8	2	8.9	7	8.3	17.7	515	10
WD1133	18X8.50-8	4	8.9	7	8.3	17.9	815	22



HI-RUN



SU05

Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WD1132	18X8.50-10	4	8.9	7	7.9	18.7	795	22
WD1033	18X9.50-8	2	6.3	7	8.8	17.9	695	12
WD1134	18X9.50-8	4	6.3	7	8.8	18.1	1040	24
WD1135	18X10.50-10	4	10.7	8.5	9.8	19.1	990	20
WD1050	20X8.00-8	2	4.4	6.5	8.1	20	600	10
WD1136	20X8.00-8	4	4.4	6.5	8.1	20	950	22
WD1137	20X8.00-10	4	10.1	6	8.1	19.9	895	24
WD1034	20X10.00-8	2	8.9	6	9.4	19.1	750	10
WD1138	20X10.00-8	4	8.9	7	9.4	19.7	1190	22
WD1139	20X10.00-8	6	8.9	7	9.4	20.1	1545	34
WD1092	20X10.00-10	2	10.1	8	9.4	19.7	735	10
WD1140	20X10.00-10	4	10.1	8	9.6	20	1160	22





SU05

Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WD1288	22X9.50-12	4	8.9	7	8.9	22	1290	24
WD1287	22X11.00-10	4	8.9	8.5	10.6	21.9	1480	22
WD1141	23X8.50-12	4	12.3	7	8.1	22.8	1120	22
WD1058	23X9.50-12	2	6.3	7	9.1	22.8	920	12
WD1142	23X9.50-12	4	6.3	7	9.1	23.4	1380	24
WD1143	23X10.50-12	2	12.3	8.5	9.8	22.8	890	10
WD1044	23X10.50-12	4	12.3	8.5	9.8	23.2	1340	20
WD1289	24X9.50-12	4	8.9	7	9.1	23.8	1500	24
WD1112	24X12.00-12	4	12.3	10.5	11.6	23.8	1710	20
WD1144	26X12.00-12	4	12.3	10.5	12.3	25.6	1780	20
WD1145	26X12.00-12	6	12.3	10.5	12.2	25.8	2450	35
WD1146	26X12.00-12	8	12.3	10.5	12.2	25.8	3020	50
WD1349	20X12-10	4	8.9	8.5	11	20	1320	20



Main Feature

- ☑ **Heavy-Duty Tread Pattern:** Designed for maximum traction on tough terrains.
- ☑ **Reinforced Sidewalls:** Offers enhanced protection against cuts and abrasions.
- ☑ **Wide Contact Area:** Distributes load evenly across the tire, reducing ground pressure and improving stability.
- ☑ **Self-Cleaning Grooves:** Efficiently clear mud and debris, maintaining consistent traction and performance.



SU12

Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WD1278	4.80/4.00-8	2	6.3	3.75	4.8	16.5	660	40
WD1185	9x3.50x4	4	4.4	2.75	3.5	9	352	50
WD1277	13X5.00-6	4	5.7	4.5	5	12.4	440	40
WD1100	16X6.50-8	2	6.9	5.375	6.4	15.7	415	14
WD1197	16X6.50-8	4	6.9	5.375	6.4	15.7	620	28
WD1216	20X8.00-8	4	6.3	6.5	8.3	19.2	950	22
WD1096	11X4.00-4	2	5	2.2	3.9	10.6	215	22
WD1180	11X4.00-5	2	5	3	3.9	10.6	210	22
WD1093	13X5.00-6	2	5.7	4.5	5	12.2	295	20
WD1151	13X6.50-6	2	6.3	4.5	5.7	12.6	310	23
WD1196	13X6.50-6	4	6.3	4.5	5.7	12.6	480	28
WD1152	15X5.50-6	2	5.7	4.5	5.4	14	365	14
WD1094	15X6.00-6	2	5.7	4.5	6.3	15	365	14
WD1155	16X7.50-8	2	7.6	5.5	7.1	16.5	480	12
WD1186	16X7.50-8	4	7.6	5.5	7.1	16.7	680	24



HI-RUN



SU12

Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WD1156	18X6.50-8	2	6.3	5.5	7.1	17.5	520	16
WD1279	18X6.50-8	4	6.3	5.5	7.1	17.7	770	28
WD1095	18X8.50-8	2	7.6	7	8.1	18.5	520	10
WD1159	18X9.50-8	2	7.6	7	9.3	17.9	695	12
WD1280	18X9.50-8	4	7.6	7	9.3	18.1	1040	24
WD1281	18X9.50-8	6	7.6	7	9.3	18.3	1320	36
WD1035	20X8.00-8	2	6.3	6.5	8.3	19.2	600	10
WD1160	20X8.00-10	2	7.6	6	8.1	19.7	595	12
WD1161	20X8.00-10	4	7.6	6	8.1	19.7	595	12
WD1162	20X10.00-8	2	7.6	7	10	19.7	760	10
WD1163	20X10.00-10	4	7.6	6	8.9	20.8	1225	24
WD1282	22X9.50-12	2	6.3	7	9.1	20.9	870	12
WD1174	22X9.50-12	4	6.3	7	9.1	21.3	1290	24
WD1283	23X9.50-12	2	6.3	7	9.3	22.4	825	10
WD1182	23X9.50-12	4	6.3	7	9.3	22.8	1230	20
WD1284	23X10.50-12	2	7.6	8.5	10.2	22.8	1320	20



Main Feature

- ✓ **Ribbed Tread Design:** Offers excellent directional stability and traction on both paved and unpaved surfaces.
- ✓ **Wide Circumferential Grooves:** Enhances water evacuation, reducing the risk of hydroplaning and improving wet performance.
- ✓ **Durable Construction:** Designed to withstand heavy loads and provide a long-lasting performance.
- ✓ **Low Rolling Resistance:** Improves fuel efficiency by reducing energy loss during movement, making it an ideal choice for various utility vehicles.

SU08



Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WD1090	11X4.00-5	4	1.9	3	3.9	10.6	325	46
WD1085	13X5.00-6	2	3.8	3.5	4.7	12.2	295	20
WD1292	13X5.00-6	4	3.8	3.5	4.7	12.7	440	40
WD1172	13X6.50-6	4	4.4	5	6.3	13.1	460	28
WD1036	15X6.00-6	2	5	4.5	6.1	14.3	365	14
WD1201	15X6.00-6	4	5	4.5	6.3	15	570	30
WD1037	16X6.50-8	2	5	5.375	6.5	15.9	415	14
WD1202	16X6.50-8	4	5	5.375	6.5	16.1	620	28
WD1091	18X8.50-8	2	5.7	7	8.3	17.7	515	10
WD1221	18X8.50-8	4	5.7	7	8.3	17.9	815	22
WD1293	18X9.50-8	4	4.8	7	8.8	18.1	1040	24



HI-RUN

Main Feature

- ✓ **Smooth Tread Design:** Ideal for turf and lawn applications where minimal ground disturbance is required.
- ✓ **Wide Footprint:** Provides excellent floatation, reducing ground compaction and ensuring even weight distribution.
- ✓ **Durable Construction:** Designed to withstand the rigors of consistent use, ensuring long-lasting performance.
- ✓ **Low Impact on Surfaces:** The smooth tread is gentle on delicate surfaces, making it perfect for lawn mowers, golf carts, and other turf equipment.



SU19

Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WD1183	9X3.50-4	4	-	2.5	3.3	9.1	352	50
WD1057	11X4.0-5	4	-	3	4.1	10.9	325	46
WD1290	11X6.00-5	4	-	5	5.3	11.1	450	42
WD1055	13X5.0-6	4	-	3.5	4.8	12.7	440	40
WD1184	13X6.50-6	4	-	4.5	6.3	13	480	28
WD1291	18X9.50-8	4	-	7	9.1	18	935	20



HI-RUN

Main Feature

- ✓ **Directional Tread Design:** Optimized for maximum grip and traction, particularly in wet conditions.
- ✓ **Noise Reduction Technology:** Variable pitch design reduces road noise, ensuring a quieter ride.
- ✓ **Enhanced Durability:** Strong sidewall construction offers resistance to cuts and abrasions.
- ✓ **Water Dispersion Channels:** Efficiently channel water away from the tire surface, enhancing wet performance.

SU14



Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WD1048	4.10/3.50-4	2	5	3.25	3.9	10.6	230	24
WD1200	4.10/3.50-4	4	5	3.25	3.9	10.8	350	50
WD1049	4.10/3.50-5	2	4.9	3.25	3.9	11.6	260	24
WD1203	4.10/3.50-5	4	4.9	3.25	3.9	11.8	380	50
WD1051	4.10/3.50-6	2	4.9	3.25	3.9	12.6	290	24
WD1204	4.10/3.50-6	4	4.9	3.25	3.9	12.8	445	50
WD1300	4.80/4.00-8	2	6.3	3.75	4.7	16.5	670	42
WD1176	480/400-8	4	6.3	3.75	4.7	16.5	670	42
WD1177	530/450-6	2	4.9	4.25	5.1	14.2	635	38



HI-RUN

Main Feature

- ✓ **Versatile All-Terrain Design:** Offers reliable traction on both paved and unpaved roads, ideal for mixed-use vehicles.
- ✓ **Deep Tread Grooves:** Provide excellent self-cleaning capabilities, ensuring consistent traction in muddy and wet conditions.
- ✓ **Durable Construction:** Engineered for longevity, with reinforced sidewalls to resist punctures and abrasions.
- ✓ **Enhanced Comfort:** The tread pattern is designed to reduce road noise, providing a quieter and more comfortable ride.



SU18

Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WD1053	13X5.00-6	2	10.1	3.5	4.6	13	295	20
WD1217	13X5.00-6	4	10.1	3.5	4.6	13.4	440	40
WD1308	16X6.50-8	4	15.1	5.375	6.4	16.5	615	28
WD1059	18X9.50-8	2	20.2	7	8.7	17.9	695	12
WD1219	18X9.50-8	4	20.2	7	8.7	17.9	1040	24
WD1056	20X10.00-8	4	21.4	8	9.5	20.3	1190	22
WD1054	23X10.5-12	2	19.9	8.5	10.2	23	890	10
WD1218	23X10.5-12	4	19.9	8.5	10.2	23	1340	20



Main Feature

- ✓ **Durable Tread Design:** Engineered for extended tread life.
- ✓ **Optimized Groove Pattern:** Ensures effective water evacuation, reducing the risk of hydroplaning.
- ✓ **Reinforced Sidewalls:** Provides additional protection against cuts and abrasions, enhancing durability.
- ✓ **Enhanced Traction:** The tread design ensures reliable grip on various surfaces, including wet and loose terrain.



SU06

Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WD1302	2.80/2.50-4	4	3.1	2.25	2.8	8.7	296	50
WD1303	4.10/3.50-4	2	5	3.25	3.9	10.6	230	24
WD1304	4.10/3.50-4	4	5	3.25	3.9	10.8	350	50
WD1089	4.10/3.50-5	4	5	3.25	3.9	11.6	260	24
WD1305	4.10/3.50-6	4	5	3.25	3.9	12.8	445	50
WD1222	4.80/4.00-8	4	6.7	3.75	4.7	16.5	670	42
WD1307	4.80/4.00-8	2	6.7	3.75	4.7	16.5	670	42
WD1306	5.30/4.50-6	6	4.4	4.25	5.1	14.6	635	38



HI-RUN

Main Feature

- ✓ **Aggressive Tread Pattern:** Provides excellent grip on both wet and dry surfaces, suitable for mixed terrain driving.
- ✓ **Durable Compound:** Ensures the tire's longevity, even in challenging environments.
- ✓ **Wide Tread Blocks:** Enhance stability and handling, especially when cornering.
- ✓ **Superior Water Dispersion:** Reduces the risk of hydroplaning by efficiently channeling water away from the contact area.

SU05

Lawn & Garden Assembly Kit



Item	Production Description	Wheel Size	Type	Bearing	Center Hub
AWD1008	15X6.00-6 4 ply tire on wheel with BUSHING KITS	6X4.50	pneumatic	3/4" or 5/8"	1.5"



HI-RUN

Main Feature

- ✓ **Heavy-Duty Tread Pattern:** Designed for maximum traction on tough terrains.
- ✓ **Reinforced Sidewalls:** Offers enhanced protection against cuts and abrasions.
- ✓ **Wide Contact Area:** Distributes load evenly across the tire, reducing ground pressure and improving stability.
- ✓ **Self-Cleaning Grooves:** Efficiently clear mud and debris, maintaining consistent traction and performance.

SU12

Lawn & Garden Assembly Kit



Item	Production Description	Wheel Size	Type	Bearing	Center Hub
AWD1009	15X6.00-6 4 ply tire on wheel with BUSHING KITS	6X4.50	pneumatic	3/4" or 5/8"	1.5"



HI-RUN

Main Feature

- ✓ **Smooth Tread Design:** Ideal for turf and lawn applications where minimal ground disturbance is required.
- ✓ **Wide Footprint:** Provides excellent floatation, reducing ground compaction and ensuring even weight distribution.
- ✓ **Durable Construction:** Designed to withstand the rigors of consistent use, ensuring long-lasting performance.
- ✓ **Low Impact on Surfaces:** The smooth tread is gentle on delicate surfaces, making it perfect for lawn mowers, golf carts, and other turf equipment.



SP900

Lawn & Garden Assembly

Item	Tire Size	Wheel Size	Type	Bearing	Center Hub
AWD1001	9X3.50-4	4X2.25	Flat free semi-pneumatic	5/8"	4.0"
AWD1002	11X4.00-5	5X3.25	Flat free semi-pneumatic	5/8"	4.9"
AWD1003	13X5.00-6	6X3.25	Flat free semi-pneumatic	3/4"	5.6"
AWD1004	13X6.50-6	6X4.50	Flat free semi-pneumatic	3/4"	7.3"
AWD1006	15X6.00-6	6X4.50	Flat free semi-pneumatic	3/4"	7.3"



HI-RUN

Main Feature

- ✓ **Ribbed Tread Design:** Provides excellent directional stability and smooth rolling, ideal for carts and light utility vehicles.
- ✓ **Durable Construction:** Built to withstand frequent use, ensuring long-lasting performance and minimal wear.
- ✓ **Wide Footprint:** Ensures even load distribution and reduces ground pressure, protecting surfaces from damage.
- ✓ **Optimized for Smooth Surfaces:** Reliable traction without damaging delicate surfaces.

SP911

Lawn & Garden Assembly



Item	Tire Size	Wheel Size	Type	Bearing	Center Hub
AWD1005	13X6.50-6	6X4.50	Flat free semi-pneumatic	3/4"	7.3"
AWD1007	15X6.00-6	6X4.50	Flat free semi-pneumatic	3/4"	7.3"



HI-RUN

Main Feature

- ✓ **Smooth Tread Design:** Ideal for turf and lawn applications where minimal ground disturbance is required.
- ✓ **Wide Footprint:** Provides excellent floatation, reducing ground compaction and ensuring even weight distribution.
- ✓ **Durable Construction:** Designed to withstand the rigors of consistent use, ensuring long-lasting performance.
- ✓ **Low Impact on Surfaces:** The smooth tread is gentle on delicate surfaces, making it perfect for lawn mowers, golf carts, and other turf equipment.



Smooth

Universal Lawn Mower Assembly

Item	Tire Size	Ply	Type	Bushings	Center Hub
PL1001	9X3.50-4	2	Pneumatic	3/4" or 5/8"	3.5"
PL1002	11X4.00-5	2	Pneumatic	3/4" or 5/8"	3.4"
PL1003	13X5.00-6	2	Pneumatic	3/4" or 5/8"	3.4"
PL1004	13X6.50-6	2	Pneumatic	3/4" or 5/8"	5.5"



HI-RUN

Main Feature

- ✓ **Smooth Tread Design:** Ideal for turf and lawn applications where minimal ground disturbance is required.
- ✓ **Wide Footprint:** Provides excellent floatation, reducing ground compaction and ensuring even weight distribution.
- ✓ **Durable Construction:** Designed to withstand the rigors of consistent use, ensuring long-lasting performance.
- ✓ **Low Impact on Surfaces:** The smooth tread is gentle on delicate surfaces, making it perfect for lawn mowers, golf carts, and other turf equipment.



Smooth

Universal Lawn Mower Assembly

Item	Tire Size	Ply	Type	Bushings	Center Hub
FF1001	9X3.50-4	/	Flat free	3/4" or 5/8"	3.5"
FF1002	11X4.00-5	/	Flat free	3/4"	3.4"
FF1004	13X5.00-6	/	Flat free	3/4"	3.4"
FF1005	13X6.50-6	/	Flat free	3/4" or 5/8"	5.5"



Main Feature

- ✓ **Smooth Tread Design:** Ideal for turf and lawn applications where minimal ground disturbance is required.
- ✓ **Wide Footprint:** Provides excellent floatation, reducing ground compaction and ensuring even weight distribution.
- ✓ **Durable Construction:** Designed to withstand the rigors of consistent use, ensuring long-lasting performance.
- ✓ **Low Impact on Surfaces:** The smooth tread is gentle on delicate surfaces, making it perfect for lawn mowers, golf carts, and other turf equipment.



Smooth

Universal Lawn Mower Assembly

Item	Tire Size	Ply	Type	Bushings	Center Hub
FF1003	11X6.00-5	/	Flat free	3/4"	5.9"



Main Feature

- ✓ **All-Terrain Tread Design:** Provides exceptional traction and stability across various surfaces.
- ✓ **Reinforced Shoulder Blocks:** Enhance cornering performance and provide additional protection against cuts and abrasions.
- ✓ **Wide Circumferential Grooves:** Efficiently channel water and slush away from the contact patch.
- ✓ **Durable Rubber Compound:** Ensures long-lasting tread life and resistance to wear and tear, making it suitable for both on-road and off-road adventures.

SU15



Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WD1052	18X8.50-8	4	7.6	7	8.5	17.7	815	22



HI-RUN

Main Feature

- ✓ **Performance Tread Design:** Engineered for high-speed stability and superior handling, providing excellent grip on both dry and wet roads.
- ✓ **Asymmetric Tread Pattern:** Optimizes traction and handling by offering different functionalities on the inner and outer sides, enhancing cornering stability.
- ✓ **Wide Circumferential Grooves:** Efficiently evacuate water to reduce the risk of hydroplaning, ensuring safety in wet conditions.



P823

Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WD1237	205/50-10	4	11.3	6.5	7.8	18.1	675	30
WD1361	205/50-10	6	11.3	6.5	7.8	7.8	835	45
WD1362	205/30-14	4	8.8	6.5	7.9	7.3	985	25



HI-RUN

Main Feature

- ✓ **Deep Chevron Tread Design:** Provides excellent traction on various surfaces, ideal for golf carts and utility vehicles.
- ✓ **Wide Footprint:** Ensures even weight distribution, minimizing turf damage and enhancing stability on uneven ground.
- ✓ **Durable Construction:** Engineered for long-lasting performance, capable of withstanding frequent use on golf courses and other outdoor environments.
- ✓ **Low Impact on Turf:** Designed to be gentle on grass, reducing the risk of turf damage with optimal grip and control.

P334



Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WD1253	22X11.00-8	4	19.5	9	10	22.2	1000	20
WD1254	22X11.00-10	4	19.9	8.5	10.1	23	1000	20



HI-RUN

Main Feature

- ☑ **Directional Tread Pattern:** Designed for superior handling and traction, offering excellent grip on both wet and dry surfaces.
- ☑ **Low Profile Design:** Enhances stability and cornering performance, making it ideal for high-performance applications.
- ☑ **Wide Grooves:** Efficiently channel water away from the contact patch, reducing the risk of hydroplaning and ensuring safety in wet conditions.
- ☑ **Durable Construction:** Built for long-lasting performance, with a focus on maintaining consistent traction and control.



P825

Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WD1166	165/65-8	4	10.1	5.375	6.7	16.7	615	45
WD2019	165/65-8	6	10.1	5.375	6.7	16.7	785	70
WD1167	205/65-10	4	11.3	6	7.9	20.5	910	35
WD2020	205/65-10	6	11.3	6	7.9	20.5	1105	50
WD2021	205/65-10	8	11.3	6	8.1	20.5	1330	70
WD2022	205/65-10	10	11.3	6	8.1	20.5	1660	90
WD1168	215/40-12	4	7.6	7	8.0	18.9	760	35
WD1169	215/50-12	4	7.6	7	8.5	21.1	950	35
WD1170	215/60-8	4	11.3	7	8.4	17.9	760	35



HI-RUN



P825

Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WD2018	215/60-8	6	11.3	7	8.7	18.1	935	50
WD1363	205/65-10	6	11.3	6	7.9	7.9	1100	50
WD1364	215/35-12	4	8.8	7	7.9	7.9	750	30
WD1365	215/35-14	4	7.6	7	8	8.0	705	30
WD1366	215/40-12	4	7.6	7	8	8.0	760	35
WD1367	215/50-12	4	7.6	7	8.5	8.5	950	35
WD1368	215/60-8	4	11.3	7	8.4	8.4	760	35



Main Feature

- ✓ **Extreme Mud-Terrain Tread:** Designed for unparalleled traction in the deepest mud and toughest off-road conditions.
- ✓ **Reinforced Sidewalls:** Provides extra protection against punctures and abrasions.
- ✓ **Self-Cleaning Design:** Engineered to shed mud and debris quickly, keeping optimal performance in tough conditions.
- ✓ **Heavy-Duty Construction:** Built to withstand the most demanding off-road challenges, delivering long-lasting durability and reliable performance.

P533



Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WD1356	13X4.00-6	2	17.6	3.25	3.9	12.2	280	22
WD1357	15X5.00-6	2	17.6	3.5	4.7	14.2	405	20
WD1358	16X6.00-8	2	16.4	4.375	6.1	16	410	14
WD1359	16X6.00-8	4	16.4	4.375	6.1	16	615	28
WD1360	4.80-8	4	16.4	3.75	4.5	16.7	435	20



Main Feature

- ✓ **Aggressive Knobby Tread:** Designed for exceptional off-road traction, ideal for tackling mud, sand, and rocky terrains.
- ✓ **Durable Construction:** Engineered to withstand the harshest conditions, providing long-lasting performance and reliability.
- ✓ **Reinforced Sidewalls:** Offers superior resistance to punctures and abrasions, ensuring durability in rugged environments.
- ✓ **Self-Cleaning Tread Design:** Effectively expels mud and debris, maintaining consistent traction and performance in challenging conditions.



P5016

Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WD1350	4.10-4	2	12.6	3.75	4	10.6	225	24
WD1351	4.10-6	2	12.6	3.75	4	12.8	290	24
WD1352	4.80-8	2	12.6	3.75	4.8	16.7	440	20
WD1353	13x5.00-6	2	12.6	3.75	4.8	12.9	290	20
WD1354	16x6.50-8	4	12.6	5.375	6.5	16	615	28
WD1355	18x6.50-8	4	12.6	5	6.6	17.9	505	20



Main Feature

- ✓ **Ribbed Tread Design:** Delivers superior directional stability and steering precision, ideal for highway use.
- ✓ **Low Rolling Resistance:** Enhances fuel efficiency by reducing energy loss during motion, making it a cost-effective choice.
- ✓ **Wide Circumferential Grooves:** Provides excellent water evacuation, reducing the risk of hydroplaning on wet surfaces.
- ✓ **Reinforced Shoulder Blocks:** Improves durability and enhances load-carrying capacity.



SU01

Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	PSI	Load/Speed index	Max Load (Lbs)
WD1065	4.80-8	4	6	3.75	4.7	16.1	60	62M	590
WD1003	4.80-8	6	6	3.75	4.7	16.1	60	71M	754



HI-RUN

SU02



Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	PSI	Load/Speed index	Max Load (Lbs)
WD1066	4.80-12	4	6	3.75	4.6	20.5	60	72M	785
WD1012	4.80-12	6	6	3.75	4.6	20.5	90	80M	990
WD1013	5.30-12	4	8.2	4.25	5.5	21.5	55	74M	840
WD1004	5.30-12	6	8.2	4.25	5.5	21.5	80	82M	1050
WD1211	5.30-12	8	8.2	4.25	5.5	21.5	105	88M	1250
WD1067	5.70-8	4	6.9	4.5	6.1	18.1	50	69M	715
WD1009	5.70-8	6	6.9	4.5	6.1	18.1	75	77M	910
WD1010	5.70-8	8	6.9	4.5	6.1	18.1	100	83M	1075



HI-RUN

Main Feature

- ✓ **Versatile Tread Pattern:** Designed for optimal performance on both paved roads and light off-road conditions.
- ✓ **Enhanced Traction:** The tread design offers superior grip, making it suitable for various weather conditions.
- ✓ **Durable Construction:** Built to withstand heavy loads and rough terrain, ensuring long-lasting performance.
- ✓ **Self-Cleaning Grooves:** Helps in maintaining traction by expelling mud and debris effectively.

SU03



Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	PSI	Load/Speed index	Max Load (Lbs)
WD1016	16.5X6.50-8	6	6.3	5	6.9	16.3	70	72M	785
WD1018	18.5X8.50-8	6	8.2	7	8.4	18.9	50	78M	940
WD1020	20.5X8.00-10	6	8.8	6	8.1	20.5	50	84M	1105
WD1002	20.5X8.0-10	10	8.8	6	8.1	20.5	90	95M	1535
WD1111	20.5X8-10	12	8.8	6	8.1	20.5	105	98M	1670





RIB

Item	Size	Ply	RIM (Inch)	Max Load (Lbs)	PSI
CT1001	4.80/4.00-8 FLAT FREE	4	8X2.5	/	/
CT1004	4.80/4.00-8	4	8X2.5	300	30
CT1005	4.00-6	4	6X2.5	300	30



Main Feature

- ✓ **Versatile Tread Pattern:** Designed for optimal performance on both paved roads and light off-road conditions.
- ✓ **Enhanced Traction:** The tread design offers superior grip, making it suitable for various weather conditions.
- ✓ **Durable Construction:** Built to withstand heavy loads and rough terrain, ensuring long-lasting performance.
- ✓ **Self-Cleaning Grooves:** Helps in maintaining traction by expelling mud and debris effectively.

RIB



Item	Size	Ply	RIM (Inch)	Max Load (Lbs)	PSI
CT1003	4.80/4.00-8 w/o wheel	4	8X2.5	300	30
CT1006	4.00-6	4	6X2.5	300	30



HI-RUN



SU301



Item	Size	Ply	RIM (Inch)	Max Load (Lbs)	PSI
WD1213	4.00-6	2	2.5	445	50
WD1214	4.00-6	4	2.5	445	50
WD1295	4.80/4.00-8	2	3.75	435	20
WD1086	4.80/4.00-8	4	3.75	670	42



Main Feature

- ✓ **Directional Tread Design:** Optimized for maximum grip and traction, particularly in wet conditions.
- ✓ **Noise Reduction Technology:** Variable pitch design reduces road noise, ensuring a quieter ride.
- ✓ **Enhanced Durability:** Strong sidewall construction offers resistance to cuts and abrasions.
- ✓ **Water Dispersion Channels:** Efficiently channel water away from the tire surface, enhancing wet performance.

STUD



Item	Size	Ply	RIM (Inch)	Max Load (Lbs)	PSI
CT1007	4.80/4.00-8	4	8X2.5	300	30
CT1010	4.10/3.50-4	4	4X2.5	300	30



HI-RUN

Main Feature

- ✓ **Directional Tread Design:** Optimized for maximum grip and traction, particularly in wet conditions.
- ✓ **Noise Reduction Technology:** Variable pitch design reduces road noise, ensuring a quieter ride.
- ✓ **Enhanced Durability:** Strong sidewall construction offers resistance to cuts and abrasions.
- ✓ **Water Dispersion Channels:** Efficiently channel water away from the tire surface, enhancing wet performance.

STUD



Item	Size	Ply	RIM (Inch)	Max Load (Lbs)	PSI
CT1008	4.80/4.00-8	4	8X2.5	300	30



HI-RUN

Main Feature

- ✓ **Durable Tread Design:** Engineered for extended tread life.
- ✓ **Optimized Groove Pattern:** Ensures effective water evacuation, reducing the risk of hydroplaning.
- ✓ **Reinforced Sidewalls:** Provides additional protection against cuts and abrasions, enhancing durability.
- ✓ **Enhanced Traction:** The tread design ensures reliable grip on various surfaces, including wet and loose terrain.

SAWTOOTH



Item	Size	Ply	RIM (Inch)	Max Load (Lbs)	PSI
CT1009	4.10/3.50-4	4	4X2.5	300	30



Main Feature

- ✓ **Durable Tread Design:** Engineered for extended tread life.
- ✓ **Optimized Groove Pattern:** Ensures effective water evacuation, reducing the risk of hydroplaning.
- ✓ **Reinforced Sidewalls:** Provides additional protection against cuts and abrasions, enhancing durability.
- ✓ **Enhanced Traction:** The tread design ensures reliable grip on various surfaces, including wet and loose terrain.

SAWTOOTH



Item	Size	Ply	RIM (Inch)	Max Load (Lbs)	PSI
CT1011	4.10/3.50-4	4	4X2.5	300	24
CT1012	4.10/3.50-6	4	6X2.5	400	24



HI-RUN

RIB

Wheelbarrow Assembly Kit



Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WB1001	8 Inch Pneumatic with grease fitting	4	2.02	4	2.5	8	176	30
WB1004	13 Inch Flat Free with grease fitting	/	2.52	6	4	13	220	/
WB1005	13 Inch Pneumatic with grease fitting	4	1.51	6	4	13	300	30
WB1007	16 Inch Flat Free with grease fitting	/	2.52	8	4	16	220	/
WB1009	16 Inch Pneumatic with grease fitting	4	1.51	8	4	16	300	30



Main Feature

- ✓ **Durable Tread Design:** Engineered for extended tread life.
- ✓ **Optimized Groove Pattern:** Ensures effective water evacuation, reducing the risk of hydroplaning.
- ✓ **Reinforced Sidewalls:** Provides additional protection against cuts and abrasions, enhancing durability.
- ✓ **Enhanced Traction:** The tread design ensures reliable grip on various surfaces, including wet and loose terrain.

STUD

Wheelbarrow Assembly Kit



Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
WB1002	10 Inch Flat Free with grease fitting	/	3.78	4	3.5	10	198	/
WB1003	10 Inch Pneumatic with grease fitting	4	2.52	4	3.5	10	300	30
WB1006	13 Inch Pneumatic with grease fitting	4	5.29	6	4	13	300	30



JK42



Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI	Load/Speed Index
WD1224	ST175/80R13	6PR	8.8	5	7.2	23.9	1360/1200	50	91/87M
WD1225	ST185/80R13	6PR	8.8	5	7.3	24.6	1480/1280	50	94/89M
WD1226	ST205/75R14	6PR	8.8	5.5	8.1	26	1760/1570	50	100/96M
WD1369	ST205/75R14	8PR	8.8	5.5	8.1	26	2040/1820	65	105/101M
WD1227	ST215/75R14	6PR	8.8	6	8.8	26.6	1870/1650	50	102/98M
WD1228	ST205/75R15	6PR	9.4	5.5	8.1	27	1820/1610	50	101/97M
WD1229	ST205/75R15	8PR	9.4	5.5	8.1	27	2150/1870	65	107/102M
WD1230	ST225/75R15	8PR	9.1	6	9.0	28.2	2540/2200	65	113/108M
WD1231	ST225/75R15	10PR	9.1	6	9.0	28.2	2830/2470	80	117/112M
WD1232	ST235/80R16	10PR	11	6.5	9.4	30.7	3520/3080	80	124/120M
WD1233	ST235/85R16	10PR	11	6.5	9.5	31.7	3640/3200	80	125/121M
WD1236	ST225/90R16	10PR	11.1	6	8.5	31.6	3520/3080	80	124/120M
WD1235	ST225/90R16	14PR	11.1	6	8.5	31.6	3900/3500	110	132/127M





WR089

Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI	Load/Speed Index
WD1336	ST205/75R14	8PR	7	5.5	8.0	25.9	2040/1820	65	105/101M
WD1337	ST205/75R15	8PR	7	5.5	8.1	26.9	2150/1870	65	107/102M
WD1338	ST225/75R15	10PR	7	6	8.8	28.1	2860/2470	80	117/112M
WD1339	ST235/80R16	10PR	7.6	6.5	9.3	30.8	3520/3080	80	124/120M



H180



Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI	Load/Speed Index
LZ1003	ST175/80D13	6PR	10.2	5	6.5	23.9	1360	50	91L
LZ1004	ST205/75D14	6PR	10.2	5.5	7.8	26.3	1760	50	100L
LZ1005	ST215/75D14	6PR	10.2	6	8.2	26.9	1870	50	102L
LZ1006	ST205/75D15	6PR	10.2	5.5	8.2	26.9	1820	50	101L
LZ1007	ST225/75D15	8PR	10.2	6	8.4	28.5	2540	65	113L



HI-RUN



H187

Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI	Load/Speed Index
WD1099	ST165/80D13	6PR	9.4	4.5	6.6	24	1230/1070	50	88/83L
WD1079	ST185/80D13	8PR	10.1	5	7.2	24.6	1710/1520	65	99/95L



HI-RUN

LQ225



Item	Size	Ply	T/D X/32	RIM (Inch)	SW (Inch)	OD (Inch)	Max Load (Lbs)	PSI
DM1009	ST175/85D14.5	12PR	8.2	6	6.9	25.9	2300	100
DM1010	ST205/85D14.5	14PR	8.8	6	6.9	27	3100	110
DM1011	ST225/75D14.5	14PR	12	6	9.2	27.5	3490	115



HI-RUN

OUR CORE VALUES



PROFESSIONAL

Sutong has over 40 years of experience in the tire industry, serving as a global resource integrator and supply chain expert, with a dedicated team providing 24-hour service worldwide.



PRECISE

Sutong ensures 90-day delivery for overseas shipments, 5-day delivery from distribution centers, and 24-hour outbound for online orders, maintaining a 98% fill rate for precise and efficient service.



PERSONAL

Sutong customizes programs for each customer, treating them like family. We personalize all our services, deeply caring about our customers' success, because their success is our success.



33402 Highway 290, Hockley TX 77447
Tel: (713) 690-5500 Fax: (713) 690-5501