



SHIELD H₂O™

BOOT & SHOE WATER REPELLING TREATMENT

DESCRIPTION AND USES

Rust-Oleum® Shield H₂O™ Boot & Shoe is a one-step, super hydrophobic, water repelling treatment designed to keep items dry longer. This crystal clear formula allows fabrics to breathe, while dramatically repelling water from the surface. Shield H₂O Boot & Shoe preserves footwear against damaging moisture without changing the look or feel.

Shield H₂O Boot & Shoe is ideal for use on leather, suede, Nubuck, canvas and more. It is suitable for use on work boots, tennis shoes, dress and casual shoes.

PRODUCT FEATURES

- Repels water
- Breatheable
- Invisible protection

PRODUCT

SKU	DESCRIPTION (11 oz. Spray)
280886	Boot & Shoe Water Repelling Treatment

PRODUCT APPLICATION

Use outdoors or in a well ventilated area. Use when temperature is above 50°F (10°C) and humidity is below 85% to ensure proper drying. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

SURFACE PREPARATION

Articles must be clean and dry.

PRODUCT APPLICATION (cont.)

APPLICATION

Do not shake. A test spray is recommended to obtain a feel for the spray pattern. Test in an inconspicuous area before application for colorfastness. Shield H₂O Boot & Shoe may enrich light material with a slightly darker tone. Rotate nozzle to "ON" position. Hold the spray bottle 8-12" from surface coating the entire boot or shoe until wet. Do not soak or allow to puddle. **NOTE:** If bubbles appear, lightly dab with a clean, lint-free rag. Re-apply seasonally or when needed. **Do not use near open flame.**

DRY & RECOAT

Dry and recoat times are based on 70°F and 50% relative humidity and will vary depending of the fabric of the boot or shoe. The coating will be odorless when dry. Allow to dry for 24 hours before exposing to water.

COVERAGE

Coverage will vary depending on the fabric: 60 square feet on smooth/light fabrics to 20 square feet on textured/heavy fabrics.

CLEAN-UP

When finished spraying, wipe off tip before storing. Properly discard empty container.

	TECHNICAL DATA	ROC-197
	SHIELD H₂O™ BOOT & SHOE WATER REPELLING TREATMENT	

PHYSICAL PROPERTIES

BOOT & SHOE WATER REPELLING TREATMENT		
Resin Type		Acrylic
Pigment Type		NA
Solvents		Mineral Spirits
Weight	Per Gallon	6.53 lbs.
	Per Liter	0.78 kg
Fill Weight		11 ounces
VOC		744 g/l (6.21 lbs./gal.)
Practical Coverage at Recommended DFT (assumes 15% material loss)		Coverage will vary depending on fabric 60 sq.ft. on smooth/light fabrics, 20 sq.ft. on textured/heavy fabrics
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	Varies depending on fabric
	Handle	Varies depending on fabric
	Full Cure	Allow to dry 24 hours before exposing to water
Shelf Life		5 years
Flash Point		100°F (38°C)
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061

Phone: 877-385-8155
www.rustoleum.com

Form: ARJ-2150
Rev.: 010421