



STANLEY® FATMAX® MAGNETIC TAPE RULES

- 11' blade standout.
- 1-1/4" wide blade for easy readability.
- AirLock® slide lock for durability and comfort.
- Mylar® film extends life of entire blade.
- Tru-Zero™ magnetic hook for accurate measurements in all positions.
- Powerful rare earth magnet securely holds to steel surfaces.
- High-impact ABS case with durable rubber holds up to heavy use.
- Plastic blade lock makes locking and unlocking easy.
- Rubber grip provides comfortable, slip-resistant hold.



Product #	Blade Length (ft)	Blade Length (m)	Blade Width (in)	Stud Markings (in)	Graduation
FMHT33865S	25	—	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
FMHT33866	26	8	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Major scale numbered in consecutive meters. Minor scale numbered in consecutive 10 cm repeated every 100 cm.

*Standout claims based on maximum performance

STANLEY® FATMAX® TAPE RULES W/ 11' BLADE STANDOUT

- 11' blade standout.
- 1-1/4" wide blade for easy readability.
- BladeArmor® coating on the first 3" maximizes durability of the blade.
- Mylar® film extends life of entire blade.
- High-impact ABS case with durable rubber holds up to heavy use.
- Plastic blade lock makes locking and unlocking easy.
- Rubber grip provides comfortable, slip-resistant hold.
- Three-rivet, corrosion-resistant Tru-Zero™ end hook for accurate measurements.



Product #	Blade Length (ft)	Blade Length (m)	Blade Width (in)	Stud Markings (in)	Graduation
33-716	16	—	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
33-725	25	—	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
33-726	26	8	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Major scale numbered in consecutive meters. Minor scale numbered in consecutive 10 cm repeated every 100 cm.
33-730	30	—	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
33-805	33	10	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Graduated in 16ths of an inch. Bottom edge: Major scale numbered in consecutive meters. Minor scale numbered in consecutive 10 cm repeated every 100 cm.
33-735	35	—	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.
33-740	40	—	1-1/4	16, 19.2	Top edge: Major scale numbered in consecutive feet. Minor scale numbered in consecutive inches after each foot. Bottom edge: Numbered in consecutive inches. Graduated in 16ths of an inch.

*Standout claims based on maximum performance

Graduated in 16ths of an inch.

STANLEY® FATMAX® KEYCHAIN TAPE RULE

- 3' blade standout.
- Polymer-coated blade withstands abrasion.
- Convenient and lightweight. Handy for quick measurements.
- Compact size fits in the pocket.
- Durable key ring makes it easy to carry anywhere.



Product #	Blade Length (ft)	Blade Width (in)	Stud Markings (in)	Graduation
FMHT33706	6	1/2	16, 19.2	Scale numbered in consecutive inches and feet. First twelve inches graduated in 32nds of an inch. Remainder in 16ths of an inch.